

TEMPO

Design by Lieve Altherr.

Reference

5770.

Application

Pendants

Installation type

Surface mounted

Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Clear blown glass diffuser

Materials

LED support: Aluminum

Diffuser: Blown-glass

Canopy: Steel

Finish



5770-18 Charcoal grey matte lacquer (ADAPTA RF 9913 WX)



5770-35 Matt brick lacquer (NCS S 4040-Y70R)




5770-58 Cream matte lacquer (RAL 7044)



5770-62 Green matte lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA, INC. 272 Fernwood Ave. Edison, NJ 08837 USA. Phone 732 417 1700 Fax 732 417 1701.
sales@vibialight.com www.vibia.com

VIBIA



Led 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 301.62 lm 75.4 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming: 1-10V Push

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0163 m³ /

Gross weight 2.5 kg. / Net weight 2.0 kg.


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 54.76 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 301.62 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 235.37 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Certificates



TEMPO

Design by Lievore Altherr.

Reference

5772.

Application

Hanging lamps

Installation type

Surface

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blow-glass diffuser

Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

Finish



5772-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



5772-35 Matt brick lacquer (NCS S 4040-Y70R)




5772-58 Matt cream lacquer (RAL 7044)



5772-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA LIGHTING, S.L.U. Barcelona, 72 - 74. 08820 El Prat de Llobregat (Barcelona - Spain). Tel 934 796 970. Fax 934 796 973.
vibia@vibia.com www.vibia.com

VIBIA



Led 2700K CRI >90 440.81 lm 110 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming 1-10V Push

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0149 m³ /

Gross weight 1.8 kg. / Net weight 1.2 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 52.97 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 292.12 lm


X=0.00m Y=0.00m Z=2.50m

Maximum value : 263.81 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Certificates



TEMPO

Design by Lievore Altherr.

Reference

5774.

Application

Hanging lamps

Installation type

Surface

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blow-glass diffuser

Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

Finish



5774-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



5774-35 Matt brick lacquer (NCS S 4040-Y70R)




5774-58 Matt cream lacquer (RAL 7044)



5774-62 Matt green lacquer (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA



Led 2700K CRI >90 440.81 lm 110 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming 1-10V Push

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0149 m³ /

Gross weight 2.0 kg. / Net weight 1.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 55.71 lm/W

Isolux : Floor

Coordinate system : CG

Light position :

Total flux : 302.04 lm

X=0.00m Y=0.00m Z=2.50m

Maximum value : 203.44 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Certificates

